

Product Name: Dye Sublimation Ink Sb52 Normal Black MSDS No.031-34W13K2C First issue: Mar 19, 2009 Page 1 of 6

Material Safety Data Sheets considered a hazardous substance according to osha 29 CFR 1910.1200.

1. Product and Company Identification

Product Name	: Dye Sublimation Ink Sb52 Normal Black
Product Code	: SPC-0584NK, SPC-585NK
General Use	: Ink jet printing ink
Product Description	: Sublimation Ink
MSDS Number	:031-34W13K2C
Manufacture	
Company Name	: Mimaki Engineering Co., Ltd
Address	: 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan
Telephone No.	: +81-268-64-2413
Importer/Distributor Estab	blished in USA
Company Name	: MIMAKI USA. INC.
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A
Telephone No.	: 1-678-730-0100
Emergency Telephone No.	: +81-268-64-2413

2. Hazards Identification

Emergency Overview	: Black liquid.
	Avoid contact with eyes or clothing. In the case of skin contact, wash
	with soap and water. Keep out of reach of children.
Potential Health Effects	
Inhalation	: Intentional exposure to ink vapors may cause respiratory irritation.
Eye Contact	: Ink contact with eye may be mildly irritating.
Skin Contact	: Ink contact with skin may cause irritation, swelling, or redness.
Ingestion	: May cause upset stomach.
Carcinogens	: No ingredients are listed by OSHA, IARC, or NTP as known or
	suspected carcinogens.
Potential Environmental	: Not available.
Effects	



Product Name: Dye Sublimation Ink Sb52 Normal Black MSDS No.031-34W13K2C First issue: Mar 19, 2009 Page 2 of 6

Material Safety Data Sheets considered a hazardous substance according to osha 29 CFR 1910.1200.

3. Composition / Information On Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Disperse dye	Trade Secret	Trade Secret	Trade Secret
2	Isopropyl alcohol	<1	67-63-0	C ₃ H ₈ O
3	Aqueous ammonia	<5	1336-21-6	NH4OH
4	Diethylene glycol	<10	111-46-6	$C_4H_{10}O_3$
5	Glycerol	10-20	56-81-5	$C_3H_8O_3$
6	Organic materials	<5	Trade Secret	Trade Secret
7	Water	balance	7732-18-5	H_2O

OSHA Hazardous : Not hazardous. Components (29 CFR 1910. 1200)

4. First Aid Measures

Inhalation	: If difficulties occur after vapour/aerosol has been inhaled, remove to
	fresh air and seek medical attention.
Eye Contact	: Wash affected eyes for at least 15 minutes under running water with
	eyelids held open.
Skin Contact	: Wash thoroughly with soap and water.
Ingestion	: Rinse mouth and then drink plenty of water.
Protection To First-Aiders	: Not available.

5. Fire Fighting Measures

Flammable Properties	: Not flammable.
Extinguishing Media	[:] water spray, dry extinguishing media, foam, carbon dioxide
Fire Fighting	: Wear full fire-fighting turn-out gear (full bunker gear) and
Instructions	respiratory protection (self-contained breathing apparatus).



Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Personal Precautions	: Wear appropriate personal protective equipment.	
Cleaning up Methods	Avoid release to the environment.	
	Absorb spillage with an inert material, then place in a chemical	
	waste container for later safe disposal. Earth may be shoveled to	
	contain spillage and to avoid contamination of sewers and water	
	cources.	

7. Handling And Storage

Handling	: Do not breathe (dust, vapor, mist, gas).
	Avoid contact with skin, eyes, or clothing.
	Wash thoroughly after handling.
	Destroy contaminated shoes in proper manner.
Storage	: Keep container tightly closed and in a cool place.
	Protect from temperatures below: 0 degree C.
	Protect from temperatures above: 40 degree C.

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name		TWA	STEL	Ceiling	Skin	SEN
1	Isopropyl alcohol	ACGIH TLV	200ppm	400ppm	N.E	N.E	N.E
2	Aqueous ammonia	ACGIH TLV	25ppm	N.E	N.E	N.E	N.E
3	Glycerol	ACGIH TLV	10mg/m3	N.E	N.E	N.E	N.E

Exposure Controls

Occupational Exposure Controls

Engineering Controls : It is better to place local exhaust equipment.

Personal Protection

Respiratory: Wear respiratory protection if ventilation is inadequate. BreathingProtectionprotection if breathable aerosols/dust are formed.





Product Name: Dye Sublimation Ink Sb52 Normal Black MSDS No.031-34W13K2C First issue: Mar 19, 2009 Page 4 of 6

Material Safety Data Sheets considered a hazardous substance according to osha 29 CFR 1910.1200.

Hand Protection	: Chemical resistant protective gloves.
Eye Protection	: Tightly fitting safety goggles(chemical goggles).
	Safety Glasses
Skin Protection	: To prevent ANY contact, wear impervious clothing such as gloves,
	apron, boots, or whole body suits made from neoprene, as appropriate.
	Protective Boots Gloves Full Suit
Environmental Exposure	Controls

: Not available.

9. Physical And Chemical Properties

Appearance	- Physical state	: liquid
	- Colour	: Black
Odour		: product specific
pH		: 7.0~9.5
Boiling Point	/ Boiling Range	: 100 degree C Water
Melting Point / Merting Range		: Not available.
Flash Point		: Not applicable.
Flammability(solid, gas)		: Not available.
Specific Gravity		: 1.00~1.20
Solubility		: Not available.
Water solubility		: complete
Viscosity		: 3.0~5.0mPa.s(20 degree C)

10. Stability And Reactivity

Conditions To Avoid : High and freezing temperatures.



Product Name: Dye Sublimation Ink Sb52 Normal Black MSDS No.031-34W13K2C First issue: Mar 19, 2009 Page 5 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Stability	: Stable
Materials To Avoid	: Not available.
Hazardous Reactions/	: No hazardous decomposition products if stored and handled as
Decomposition Products	prescribed/indicated.

11. Toxicologocal Information

Acute Toxicity	: Not available.
Eye Irritation	: May cause eye irritation.
Skin Irritation	: May cause skin irritation.
Sensitization	: Not available.
Mutagenicity	: Not available.

12. Ecological Information

Ecotoxicity	: Not available	
Persistence And	And : Not available.	
Degradability		
Bioaccumulative	: Not available.	
Potential		
Other Adverse Effects	: Not available.	

13. Disposal Considerations

Must be dumped or incinerated in accordance with local regulations. Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.
<u>Do not dump this product into sewers, on the ground or into any body</u> of water.

14. Transport Information

Not classified as a dangerous good under transport regulations. (USDOT / IMDG / IATA / ICAO)



Product Name: Dye Sublimation Ink Sb52 Normal Black MSDS No.031-34W13K2C First issue: Mar 19, 2009 Page 6 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

15. Regulatory Information

OSHA Status	: Not hazardous.
TSCA Status	: released / listed
SARA Title III	
Section 311/312	: Not hazardous.
(40 CFR 370)	

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and dose not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

Revision history

Version	Date	Content
1.0	Mar 19, 2009	First issue.