

MSDS No. 031-34U010B First issue: 2008/6/20

Revised:

## **Material Safety Data Sheets**

Page 1 of 7

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### **Product and Company Identification**

**Product Name** : UV Ink Washing Liquid

**Product Code** : SPC-0384,0385

General Use : For ink jet

: UV curable ink **Product Description MSDS** Number : 031-34U010B

Manufacture

Company Name : Mimaki Engineering Co., Ltd

: 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan Address

Telephone No. : +81-268-64-2413

Importer/Distributor Established in USA

Company Name : MIMAKI USA. INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A

Telephone No. : 1-678-730-0100 Emergency Telephone No. : +81-268-64-2413

#### **Hazards Identification**

: ADVERSE HUMAN HEALTH HAZARDS **Emergency Overview** 

Irritating to eyes, respiratory system and skin.

: ENVIRONMENTAL EFECTS

Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

**Potential Health Effects** 

Inhalation : Irritating to respiratory system.

**Eye Contact** : Irritating to eyes. Skin Contact : Irritating to skin.

: No ingredients are listed by OSHA, IARC, or NTP as known or Carcinogens

suspected carcinogens.

Potential Environmental

: Very toxic to aquatic organism. May cause long-time adverse effects

in the aquatic environment. **Effects** 



MSDS No. 031-34U010B First issue: 2008/6/20

Revised:

# Material Safety Data Sheets

Page 2 of 7

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

**Hazard Label** 

Xi: Irritant



HMIS Rating (scale 0 - 4)

NFPA Rating (scale 0 – 4)

Health = 1

Flammability= 1

Physical Hazard = 1



Health = 1 Flammability = 1 Instability =1



### 3. Composition / Information On Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Acrylates	> 90	Registered	-
2	Additives	< 15	Registered	-

### 4. First Aid Measures

Inhalation : Remove the victim from the contamination immediately to fresh air.

Keep the victim warm and quiet and arrange for transport to the nearest medical facility for examination and treatment by a

physician as soon as possible.

Eye Contact : Gently rinse the affected eyes with clean water for at least 15

minutes.

Remove contact lenses if easily possible.

And refer for medical attention.

Skin Contact : Remove all contaminated clothing, shoes and socks from the affected

areas as quickly as possible. Wash the affected area under running

water using a mild soap.

If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by physician as soon as

possible.

Ingestion : Never give anything by mouth to someone who is unconscious or

convulsing. If the victim is responsive, give him one or two glasses of

water. And refer for medical attention.



MSDS No. 031-34U010B First issue: 2008/6/20

Revised:

### Material Safety Data Sheets

Page 3 of 7

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### 5. Fire Fighting Measures

Flammable Properties Autoignition temperature : No Data Available

Flash Point : 111 degree C

[Test Method: Cleveland Open Cup]

Flammable Limits – LEL : No Data Available Flammable Limits – UEL : No Data Available

Extinguishing Media : Dry chemical powder, form or dioxide. Fire Fighting : Fight fire from maximum distance.

Instructions Shut off fuel to fire if possible to do so without hazard.

Wear full fire-fighting turn-out gear (full bunker gear) and

respiratory protection (self-contained breathing apparatus).

#### 6. Accidental Release Measures

Shut off all sources of ignition; No smoking or flames in area.

Wear proper protective equipment.

Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools.

Prevent spills from entering sewers, watercourses or low areas.

Do not wash away into shower or waterway.

### 7. Handling And Storage

Handling : Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Only use tools and equipment resistant to organic solvents.

Do not flush to sewer or waterways.

Storage : Store product in tightly closed original containers in dry and cool

place protected from sunlight fluorescent light, preferably at below 25

degree C on impermeable ground. Keep away from sources of ignition.

### 8. Exposure Controls / Personal Protection

Control parameters of : Not established.

ingredients

**Exposure Controls** 

Occupational Exposure Controls

Engineering Controls : Do not use in areas without adequate ventilation.



MSDS No. 031-34U010B First issue: 2008/6/20

Revised: Page 4 of 7

# Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Personal hygiene and protective equipment

: Follow the general guidelines of good industrial hygiene. Avoid any

contact with the product. Never breathe product vapor.

**Personal Protection** 

Respiratory : Chemical cartridge respirator with an organic vapor cartridge.

Protection



Hand Protection : Impermeable gloves.

Gloves

Eye Protection : Chemical safety glasses.

Safety Glasses

Skin Protection : Long sleeve clothing, resistant to solvents.



### 9. Physical And Chemical Properties

Appearance - Physical state : liquid

- Color : Non Color

Odor : Characteristic odor : Not applicable pН Boiling Point / Boiling Range : No data available Melting Point / Melting Range : No data available Flash Point : 129 degree C : No data available **Auto-Ignition Temperature Explosive Properties** : No data available Flammable Limits : No data available Vapour Pressure : Not available **VOC** : Not applicable

VOC : Not applicable Specific Gravity : No data available

Solubility : Miscible in organic solvent

Water solubility : Insoluble

Viscosity : 4 – 5 mPa·s (25 degree C) Surface tension : 28 – 33 mN/m (25 degree C)



MSDS No. 031-34U010B First issue: 2008/6/20

Revised:

## **Material Safety Data Sheets**

Page 5 of 7

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### 10. Stability And Reactivity

Conditions To Avoid : Heat, sunlight (may result in polymerization)
Stability : Stable under the usual handling conditions.

Materials To Avoid : Oxidizing agents, strong bases, and transition metals (possible

polymerization)

### 11. Toxicologocal Information

Acute Toxicity : Not available

Eye Irritation : The product may cause a moderate irritation to the eyes, followed by

burning sensation, tearing, and redness.

Skin Irritation : Skin contact may result in delayed irritation and blistering.

Sensitization : Not available

Mutagenicity : Not available

Carcinogenicity : Not available

Others : No significant symptoms of any adverse health hazard is expected to

occur by ingestion of the product.

Due to the low vapor pressure, inhalation is no primary route of entry. Irritations of the respiratory tract may be caused by inhalation of

product vapors or mists in high concentration (List 1).

### 12. Ecological Information

No data is available about ecotoxicological potential of the product.

Never release product into the environment. Decant and purify polluted waste before its release into the drains.

Ecotoxicity : Not available
Persistence And Degradability : Not available
Bioaccumulative Potential : Not available
Other Adverse Effects : Not available



MSDS No. 031-34U010B First issue: 2008/6/20

Revised:

## **Material Safety Data Sheets**

Page 6 of 7

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

### 13. Disposal Considerations

: Scrap materials may be disposed by licensed contractor or burn in approved incinerator. Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

### 14. Transport Information

Perform prevention of collapse of cargo surely.

Follow all regulation in your country.

Us Department of Transportation (DOT)

**Hazardous Materials** : Not Applicable

Sea Transport (IMDG)

: 9 Miscellaneous dangerous substances and articles. Class

Packing Group (PG)

**UN Number** : 3082 Marine Pollutant : No

Air Transport (ICAO/IATA)

: 9 Miscellaneous dangerous substances and articles. Class

Packing Group(PG)

**UN Number** : 3082

### 15. Regulatory Information

Follow all regulations in your country.

: This product is NOT considered hazardous under the OSHA Hazard **OSHA Status** 

Communication Standard (29 CFR 1910.1200).

: All components comprising this product are listed on or exempt from **TSCA Status** 

TSCA inventory.

**SARA Title** 

Section 302 - Extremely Hazardous Substance (EHS)

(40 CFR 355) : This product does not contain any chemicals regulated under Section 302

(40 CFR 355) as extremely hazardous substances.

Section 304 - Comprehensive Amendments and Reauthorization and Liability Act

(40 CFR 302) (CERCLA)

> : This product does not contain any chemicals regulated under Section 304 (40 CFR 302) as hazardous chemical for emergency release notification

(CERCLA List).



MSDS No. 031-34U010B First issue: 2008/6/20

Revised: Page 7 of 7

### **Material Safety Data Sheets**

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Section 313 - Toxic Chemical List (TCL)

(40 CFR 372) : This product does not contain a toxic chemicals for under Section 313

(40 CFR 372.65)

Others

California : This product does not contain any chemicals currently listed on the

Proposition 65 California list known Carcinogens and Reproductive Toxins.

Warning Sign : Xi (Irritant)

Risk information : Irritating to eyes, respiratory system and skin.

Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Safety Information : Keep out of the reach of children.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be

specified by the manufacturer).

Do not empty into drains, dispose of the material and its container at

hazardous or special waste collection points.

If swallowed, seek medical advice immediately and show this container

label.

#### 16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and dose not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

#### **Revision history**

Version	Date	Content
1.0	2008/06/20	First issue