

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

SECTION I

Manufactured:
Press Smart Printing Products, LLC.
Palinfield, IL

TRADE NAME: Silli Slip

For distribution through:
Lehman, Inc.
Elk Grove Village, IL 60007

EMERGENCY PHONE 800-345-6297
4/16/2013

SECTION II

Hazardous Ingredients / Identity Information

Table with 5 columns: Hazardous Components, OSHA PEL, ACGIH TLV, OTHER LIMITS, %. Row 1: PETROLEUM NAPHTHA, 500 ppm, LC(low) (cats), 10 gms/M³ - 2.5 Hrs.

UN1268
CAS # 8052-41-3
HMIS RATING: H-1, F-1, R-0, PP-B
DOT Classification - 55
NMFC # 48580 SUB 3
VOC'S = 70%

Ingredients in this formulation are on the TSCA inventory list.

SECTION III

Physical / Chemical Characteristics

Boiling Point: 316 - 360°F Specific Gravity (H2O = 1) .807
Vapor Pressure: @37.8 °C= 8mm Melting Point: N/A
Vapor Density (air = 1): 4.7 Evaporation Rt(Butyl Acetate = 1) Lower
Solubility in water: Insoluble
Appearance and Odor: Colorless, slightly viscous liquid with pleasant odor

SECTION IV

Fire and Explosion Data

Flash Point (Method Used) T.C.C. 110°F
Flammable Limits: LEL 1.0 UEL 6.0
Extinguishing Media Foam, CO2, Water fog, Dry Chemical

Special Fire Fighting Procedures Water spray can be used to keep containers cool.

Unusual Fire and Explosion Hazards: None

::

SECTION V

Reactivity Data

STABILITY: STABLE XX CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents.
Can react with chlorine or oxygen.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon Monoxide, Oxides of Silicone, Nitric and Sulfuric Acids, Carbon Dioxide.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR XX CONDITIONS TO AVOID: N/A

SECTION VI

HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION?	PRIMARY	SKIN	INGESTION
HEALTH HAZARDS (ACUTE & CHRONIC): ACUTE LOCAL		SECONDARY	N/A

CARCINOGENICITY: Unknown	NTP?	IARC MONOGRAPHS?	OSHA REGULATED?
-----------------------------	------	------------------	-----------------

SIGNS AND SYMPTOMS OF EXPOSURE:

Dizziness, headache,. Petroleum distillates are central nervous system depressants. nose & throat irritations may occur from inhalation. prolonged skin contact may cause defatting and dermatitis. Eye contact causes conjunctivitis.

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY EXPOSURE: Open sores. Dermatitis conditions.
any breathing conditions.

EMERGENCY AND FIRST AID PROCEDURES: EYES: Flush with water until clear.

Skin: Wash with mild soap & water. Ingestion: Do not induce vomiting. Consult medical attention.

SECTION VII

PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate ignition sources, contain spill. Absorb small spills with oil dry compounds(inert). large spills pump to container for recovery.

WASTE DISPOSAL METHOD: Consult State, Local and Federal agencies for compliance.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at ambient temperatures.
Avoid physical damage to containers. Keep containers closed during storage.

SECTION VIII

CONTROL MEASURES

Respiratory Protection: Use full face respirator with organic cartridge.

VENTILATION	LOCAL EXHAUST	TO OUTSIDE	SPECIAL N/A
	MECHANICAL	DUST & SPARK PROOF	OTHER N/A

PROTECTIVE GLOVES: Neoprene recommended, PVC coated.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety goggles recommended, rubber apron.

WORK/HYGIENIC PRACTICES: Wash hands after use. Keep area clean.